

SURE SHADE®

SURE SHADE® Basic 100F L3 W

Dimension maximums* *kpa dependent

Width : 4800 mm (special widths available)

Height : 4800 mm (special heights available)

(width of blinds includes lateral guides and height of blinds include mount box/pelmet)

Maximum area of the blind

Electric motor : 24 sq. m.

Operation of the blind

Electric motor : Motor each blind with exclusive Magic Button wireless

Colour of Slats

Standard colour set with structured finish to resist abrasion and enhance colour luminosity

metallic silver : (VSR 140S) white : (VSR 010S)

beige : (VSR 240S) metallic bronze : (VSR special)

Full VSR colour range or RAL colour available for quantity from 70m squared.

Blind materials

Aluminium slats : 100mm degreased and chromated, two sided and edge structured colour surface polyester coating

Width of slat : 100mm, slat cover 92mm

Head box : Extruded aluminium 56 x 58 mm, 10um clear anodised with sound suppression engagement channels

Pelmet (optional) : Engineered extruded aluminium, 25um clear anodised, self supporting to 5 metre with isolating rubber head rail top hat & bottom motor vibration/noise suppression twist snap mount

Bottom rail : Extruded section aluminium, 25um clear anodised, complete with 316 stainless steel end caps & 6mm stem drop forged guide pins

Lifting system : Technically superior 8mm Texband, especially coated fabric, protected against abrasion, UV light and rot, via punched and drawn 8.5mm hole in slat, black or grey

Slat support system: Ladder string, double woven *aramid* (no stretch), reinforced, double stitched polyester high fast coloured fibres, thermo fixed, artificial fold points, black. Omega tab fixing of cross string.

Lateral guides : 4mm o/a UV stabilised black PA 12 biobased engineered polymer plastic coated stainless steel stranded cable via punched and drawn 30mm x 8mm slot in slat, spring or threaded screw module with aluminium bottom fix.