

SURE SHADE®

SURE SHADE® Ultimate 120S H3 E

Dimension maximums*

	: *kpa dependent
Width	: 4800 mm (special widths available)
Height	: 5000 mm (special heights available)

(width of blinds includes lateral guides and height of blinds include mount box/pelmet) *kpa dependent

Maximum area of the blind

Electric motor	: 24 sq. m.
----------------	-------------

Operation of the blind

Electric motor	: Motor each blind with <u>exclusive Magic Button</u> hand remote transmitter
----------------	---

Colour of Slats

Standard colour set with structured finish to resist abrasion and enhance colour luminosity

metallic silver	: (VSR 140S)	metallic grey alu	: (VSR 907S)
metallic bronze	: (VSR special)	anthracite grey	: (VSR 716S)

Full VSR colour range or RAL colour available for quantity from 70 metre squared.

Blind materials

Aluminium slats	: <u>120mm S shaped</u> with rolled profile and <u>integrated grey Keder</u> for light blackout*, (*kpa dependent) degreased and chromated, two sided simultaneously structured high UV stability characteristics, wet roller and oven cured at 200 degree celsius colour coating.
Width of slat	: <u>120mm, slat with a cover of 107mm</u>
Head box	: Extruded aluminium 56 x 58 mm, 10um clear anodised with sound suppression engagement channels
Pelmet (optional)	: Engineered extruded aluminium, 25um clear anodised, self supporting to 5+ metre with isolating rubber head rail top hat & bottom motor vibration/noise suppression twist snap mount & secured by <u>316 stainless M10x40 grub screws & nuts</u>
Pelmet slat cover	: Extruded aluminium with engagement profile into pelmet, 25um clear (optional) anodised, removeable independently of pelmet and head box
Bottom rail	: Engineered extruded section aluminium, 25um clear anodised complete with <u>316 stainless steel manufactured end caps & 6mm stem drop forged guide pins & securing M10x40 grub screws & nuts</u>
Lifting system	: Technically superior 8mm <u>Texband</u> , especially coated fabric, protected against abrasion, UV light and rot, via punched and drawn <u>slot</u> in slat, in slate grey or black
Slat support system	: Advanced 107mm <u>Hagofix</u> spigot tape with stainless steel hook connector technology. Woven grey polyester tape with double <u>aramid</u> reinforcement, UV resistant synthetic connecting element with exact fold points for perfect slat closure. Mechanically injected slat stainless steel hooks <u>rated to 20daN</u> .
Lateral guides	: <u>Zamac pins (zinc with alloys of aluminium, magnesium and copper)</u> <u>riveted</u> to alternate slats engaged with 40mmx80mm, extruded aluminium side guides, 25um clear anodised, with plastic side inserts to reduce noise. The verticals to be self supporting to 5 metre & fully integrated with pelmet by way of engaged brackets and internal slide nut with <u>316 stainless M10x40 grub screws & nuts</u> .