

SURE SHADE®

SURE SHADE® Ultimate 120S H3 W

Dimension maximums*

	*kpa dependent
Width :	4800 mm (special widths available)
Height :	5000 mm (special heights available)

(width of blinds includes lateral guides and height of blinds include mount box/pelmet) *kpa dependent

Maximum area of the blind

Electric motor :	24 sq. m.
------------------	-----------

Operation of the blind

Electric motor :	Motor each blind with <u>exclusive Magic Button</u> wireless
------------------	--

Colour of Slats

Standard colour set with structured finish to resist abrasion and enhance colour luminosity

metallic silver :	(VSR 140S)	metallic grey alu :	(VSR 907S)
metallic bronze :	(VSR special)	anthracite grey :	(VSR 716S)

Full VSR colour range or RAL colour available for quantity from 70 metre squared.

Blind materials

Aluminium slats :	<i>120mm S shaped with rolled profile and <u>integrated grey Keder for light blockout*</u>, (*kpa dependent) <u>degreased and chromated</u>, two sided <u>simultaneously structured high UV stability characteristics</u>, wet roller and oven cured at 200 degree celsius colour coating.</i>
Width of slat :	<i>120mm, slat with a cover of 107mm</i>
Head box :	<i>Extruded aluminium 56 x 58 mm, 10um clear anodised with sound suppression engagement channels</i>
Pelmet (optional) :	<i>Engineered extruded aluminium, 25um clear anodised, self supporting to 5+ metre with isolating rubber head rail top hat & <u>secured by 316 stainless M10x40 grub screws & nuts</u></i>
Bottom rail :	<i>Engineered extruded section aluminium, 25um clear anodised complete with <u>316 stainless steel manufactured end caps & 6mm stem drop forged guide pins.</u></i>
Lifting system :	<i>Technically superior 8mm <u>Texband</u>, especially coated fabric, protected against abrasion, UV light and rot, via punched and drawn <u>slot</u> in slat, in slate grey or black.</i>
Slat support system :	<i>Advanced 107mm <u>Hagofix</u> spigot tape with stainless steel hook connector technology. Woven grey polyester tape with double <u>aramid</u> reinforcement, UV resistant synthetic connecting element with exact fold points for perfect slat closure.</i>
Lateral guides :	<i>Mechanically injected slat stainless steel hooks <u>rated to 20daN</u>. 4mm o/a UV stabilised black <u>PA 12 biobased engineered polymer plastic coated stainless steel stranded cable via punched and drawn 8.5mm hole</u> in slat, spring or threaded screw module with aluminium bottom fix.</i>