

SURE SHADE®

SURE SHADE® Basic 80C L1 E

Dimension maximums* *kpa dependent

Width : 4800 mm (special widths available)

Height : 4800 mm (special heights available)

(width of blinds includes lateral guides and height of blinds include mount box/pelmet)

Maximum area of the blind

Electric motor : 24 sq. m.

Minimum width of blind

Electric motor : 600 mm

Operation of the blind

Electric motor : Motor each blind with exclusive Magic Button hand transmitter

Colour of Slats

Standard colour set with structured finish to resist abrasion and enhance colour luminosity

metallic silver : (VSR 140S), white : (VSR 010S)

beige : (VSR 240S) metallic bronze : (VSR special)

Full VSR colour range or RAL colour available for quantity from 70m squared.

Blind materials

Aluminium slats : 80mm C shape with 4mm rolled profile, degreased and chromated, two sided structured colour surface polyester coating

Width of slat : 80mm, slat cover 72mm

Head box : *Extruded aluminium 56 x 58 mm, 10um clear anodised with sound suppression engagement channels*

Pelmet (optional) : Engineered extruded aluminium, 25um clear anodised, self supporting to 5 metre with isolating rubber head rail top hat & bottom motor vibration/noise suppression twist snap mount

Bottom rail : Extruded section aluminium, 25um clear anodised, complete with 316 stainless steel metal end caps and guide pins

Lifting system : Technically superior 8mm Texband, especially coated fabric, protected against abrasion, UV light and rot, via punched and drawn slot in slat , black or grey

Slat support system : Ladder string, double woven *aramid* (no stretch), reinforced, double stitched polyester high fast coloured fibres, thermo fixed, artificial fold points, black

Lateral guides : *Zamac pins (zinc with alloying elements of aluminium, magnesium and copper). riveted* to alternate slats engaged with extruded aluminium side guides, clear anodised, with plastic side inserts reducing noise